

OMNIPAQ TH63

TRANSMITTER | 8 BUTTON

Compatible with Panther and Puma

Buttons

Display

Frequency

Radio frequency band

Frequency management

Radio frequency output power

Radio communication

Battery

Number of batteries

Charging

Weight

Dimensions (w x h x d)

Protection

Operating temperature

Charging temperature

Safety level

On/off switch

Smartphone Connectivity

Smartphone App FieldManager™

RFID

Easy plug-in abilities

Acceleration sensor

Buzzer

Yes

8 2-step buttons

No

2,4 GHz, 16 channels

2405 - 2480 MHz

Direct Sequence Spread Spectrum (DSSS)

EIRP: <12dBm (15.85mW) FCC+IC Max EIRP: <18dBm (63mW)

Duplex when using Puma protocol, simplex when using Panther protocol

3.7 V/ 2000 mAh Li-ion, rechargeable

1 changeable

No internal charging

270 grams, without battery

85x193x43 mm

IP65

-20 to +55 degrees Celcius

+10 to +35 degrees Celcius

Ple, CAT4, SIL3 on stop function

Yes

Yes IEEE 802.15

Yes (Android/iOS)

No

Yes

Yes

No

Changes and errors reserved.

PLEASE VISIT OUR WEBSITE FOR OUR WORLDWIDE LOCATIONS

teleradio.com

SAFE • SMART • STRONG





OmniPAQ TH63



NEW
OMNIPAQ TH63
with FieldManager™
smartphone App
connectivity

TECHNICAL DATA

AN **ALLGON®** COMPANY